

Medrag - PVA-01

Transport Vacuum Aspirator



Portable Aspirator

KEY FEATURES



INTEGRATED VACUUM PUMP



SAFE & PRECISE ASPIRATION



ADJUSTABLE VACUUM PRESSURE



VACUUM GAUGE

- ✓ Provides reliable and powerful suction with its built-in vacuum pump.
- ✓ Offers precise control tailored to your needs with adjustable vacuum pressure.
- ✓ The constantly visible pressure gauge makes it easy to monitor the vacuum level.
- ✓ The push-button vacuum control ensures practical and controlled operation.
- ✓ The anti-overflow valve system protects the device and the surrounding area.
- ✓ The replaceable filter and graduated collection jar ensure hygienic use and allow for easy monitoring of fluid levels.



Technical Specifications

Property	Value / Description
Max. Flow Rate	30 liters / min
Vacuum Range	50mmHg-600 mmHg
Noise Level	65 dB
Dimensions	239(w) x 159(h) x 117(D) mm
Weight	3.96 kg (bags and accessories included)
Electrical Requirements	12VDC 4A 60W
Battery	5200 mAh, integrated rechargeable battery
Working Time on Battery	45 minutes
Collection Bottle Capacity	1000 ml (cc) Disposable or Reusable
Operating Temperature Range	-0,4°F (-18°C) to 140°F (60°C)
Operating Relative Humidity	0-95%
Operating Atmospheric Pressure	10.2 Psi (70 kPa) - 15.4 Psi (106 kPa)
Storage and Transport Temperature Range	-0,4°F (-18°C) to 140°F (60°C)
Storage and Transport Relative Humidity	0-95%
Storage and Transport Atmospheric Pressure	7.3 Psi (50 kPa) - 15.4 Psi (106 kPa)
Accessories	1,2 liter reusable transparent break-resistant graded polycarbonate collection bottle, Disposable bacteria filter, non-metallic pharyngeal suction tip, Silicone tubing, 12 V Car Charger Kit



MODÜL GRUP MÜHENDİSLİK MED.A.Ş.

Merkez: Ovacık Mah. 2035. Sk.No:1/2A Keçiören/ANKARA
 Şube: İvedik Osb.Mh.2224.Cd.No:1/25 Y.Mahalle/ANKARA
 Tel:0312 354 03 73 Fax:0312 354 75 45
 Mail:info@modulmuhendislik.com.tr